





coviva characteristics:

- coviva allows for setup without any special tools, by only using the buttons on the products.
- All micro modules are equipped with two inputs for potential-free contacts
- Frequency: 868.3 MHz wireless KNX
- Bi-directional communication between products
- Linked to coviva app controller, it enables remote and local control by smartphone or tablet.
- Made in France

 **Easy pairing**
Easy pairing mode where 1 colour = 1 function

 **Without works**
Wireless commands for sites; no need for wireways.

App Controller

Upgrade your coviva system and manage all your applications locally or remotely from your smartphone or tablet by using the App controller.



For more information visit us

www.coviva.co.za

coviva

Wireless Home Control






Connect and manage your home through the wireless **KNX** RF system.




:hager

Wirelessly manage and control ...



Control

-  Lighting
-  Dimming of lights (excluding CFL)
-  Roller blinds and curtains

Functions






-  Switch
-  Timer
-  Raise / lower
-  Scene setting
-  Group controls
-  All free contact

And also...

-  Ceiling fan, automatic sprinkler..
-  Garage doors, gates, geysers etc.

Micromodules




Transmitters

			
Product code	TRC301B	TU4xx	TRM702A
Installation type	Surface door contact	Remote	In wall
Channels	1	2, 4 or 6	2
			flat wireless transmitter (Available in various colours) 
			8565XXXX
			Surface
			1 or 2 gang

All units are delivered with batteries included. (Estimated battery lifespan is 5 years)



Transmitters / Receivers

Product Code	Connection Type	Incandescent Lamps	Halogen Lamps	Halogen Tbt	CFI	Non Dimmable Led	Dimmable Led	Inductive Load Ac	Inductive Load Dc
Dimming application 									
TRM691E	Phase only	10 to 200W	10 to 200W	10 to 175VA	-	-	3W to 50W	-	-
Shutters, blinds and roller doors 									
TRM692G	Phase & Neutral	-	-	-	-	-	-	3A	-
Switching applications 									
TRM690G	Phase only	10 to 200W	10 to 200W	10 to 175VA	-	-	3W to 50W	-	-
TRM693G	Phase & Neutral	500W	500W	250VA	150W	150W	150W	3A	-
TRM694G	Phase & Neutral	600W	600W	600VA	40W	40W	40W	4A	4 A @ 12V or 2 A @ 24 V
TRB201	Phase & Neutral	2300W	1500W	1500VA	100W	100W	-	16A	-

COVIVA : SMART HUB FOR IOS OR ANDRIOD APP CONTROL	TPK100	-
OPTIONAL WIFI DONGLE FOR COVIVA	TKH180	-

All units have an operating voltage of 230V (+/- 10%), and are installed in the existing wall box. The range of all transmitter/ receiver products are 100m free field and 30m between 2 concrete walls. All 230V phase and neutral powered modules work as repeaters for the knx wireless network.